

(19)



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11)

**EP 0 831 546 A2**

(12)

## EUROPEAN PATENT APPLICATION

(43) Date of publication:  
25.03.1998 Bulletin 1998/13

(51) Int. Cl.<sup>6</sup>: H01Q 1/36, H01Q 1/38

(21) Application number: 97116099.9

(22) Date of filing: 16.09.1997

(84) Designated Contracting States:  
AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC  
NL PT SE  
Designated Extension States:  
AL LT LV RO SI

(30) Priority: 20.09.1996 JP 250142/96

(71) Applicant:  
MURATA MANUFACTURING CO., LTD.  
Nagaokakyo-shi Kyoto-fu 226 (JP)

(72) Inventors:  
• Suesada, Tsuyoshi  
Nagaokakyo-shi, Kyoto-fu (JP)  
• Kanba, Seiji  
Nagaokakyo-shi, Kyoto-fu (JP)  
• Tsuru, Teruhisa  
Nagaokakyo-shi, Kyoto-fu (JP)

(74) Representative:  
Schoppe, Fritz, Dipl.-Ing.  
Schoppe & Zimmermann  
Patentanwälte  
Postfach 71 08 67  
81458 München (DE)

### (54) Chip antenna and antenna device

(57) A chip antenna (10) comprising a substrate (11) comprising at least one material selected from a dielectric material and a magnetic material, at least one conductor (12) formed at least one of in the interior of the substrate (11) and on the surface of the substrate (11), at least one feeding terminal (13) provided on the surface of the substrate (11) and connected to an end of the conductor (12) for applying a voltage to the conductor (12), and at least one capacitor-forming conductor (14) provided at least one of in the interior of the substrate (11) and on the surface of the substrate (11) and connected to the other end of the conductor (12). An antenna device (40) comprising an antenna main body (41) and a mounting board (42) for mounting the antenna main body (41) is also disclosed. The antenna main body (41) may have the same configuration as the above-described chip antenna (10).




FIG. 1

EP 0 831 546 A2

## Description

## BACKGROUND OF THE INVENTION

## 1. Field of the Invention

The present invention relates to chip antennas and antenna devices. In particular, the present invention relates to a chip antenna and an antenna device used in mobile communication and mobile communication devices for local area networks (LAN).

## 2. Description of the Related Art

Figure 12(a) is a plan view of a conventional chip antenna and Figure 12(b) is a cross-sectional view taken along section line A-A of Figure 12(b). This chip antenna 1 is of a microstrip type and is provided with a radiation electrode 3 as an antenna element on a main surface of a planar dielectric substrate 2 and a ground electrode 4 on the other main surface of the substrate 2. The dielectric substrate 2 is a planar rectangular member comprising a dielectric ceramic material such as aluminum or a polymeric compound. The radiation electrode 3 is smaller than the dielectric substrate 2, whereas the ground electrode 4 is formed on the entire main surface of the dielectric substrate 2. The ground electrode 4 is connected to an external conductor 6 of a coaxial cable 5 and the radiation electrode 3 is connected to a central conductor 7 at the feeding point 8.

The resonance frequency  $f$  and the bandwidth BW of the chip antenna 1 are determined by the following equations in response to the shape of the antenna:

$$f = Co/2 \cdot (\epsilon)^{1/2} \cdot l \quad (1)$$

$$BW = (K \cdot d \cdot f)/\epsilon \quad (2)$$

wherein  $Co$  is the velocity of light,  $\epsilon$  is the relative dielectric constant of the dielectric substrate 2,  $l$  is a vertical length of the radiation electrode 3 as the antenna element,  $K$  is a constant of proportionality, and  $d$  is the thickness of the dielectric substrate 2 shown in Figure 12(b).

When the resonance frequency  $f$  is constant, use of a material having a large relative dielectric constant as the dielectric substrate 2 is capable of reducing the vertical length  $l$  of the radiation electrode 3, thus miniaturizing the chip antenna 1.

When the resonance frequency, however, is constant in the above-mentioned conventional antenna, a miniaturized antenna having a large relative dielectric constant has a narrow bandwidth and is not suitable for mobile communication devices which requires a broad bandwidth. Miniaturization of the antenna is therefore barely compatible with a broad bandwidth.

## SUMMARY OF THE INVENTION

It is an object of the present invention to provide a compact chip antenna and an antenna device which have a broad bandwidth.

In accordance with the present invention, a chip antenna comprises a substrate comprising at least one material selected from a dielectric material and a magnetic material, at least one conductor formed at least one of in an interior portion of the substrate and on a surface of the substrate, at least one feeding terminal provided on the surface of the substrate and connected to a first end of the conductor for applying a voltage to the conductor, and at least one capacitor-forming conductor provided in at least one position of the interior and the surface of the substrate and connected to a second end of the conductor.

In accordance with another aspect of the present invention an antenna device comprises an antenna main body and a mounting board for mounting the antenna main body; the antenna main body comprising a substrate comprising at least one material selected from a dielectric material and a magnetic material, at least one conductor formed at least one of in an interior portion of the substrate and on a surface of the substrate, at least one feeding terminal provided on the surface of the substrate and connected to a first end of the conductor for applying a voltage to the conductor, and at least one free terminal provided on the surface of the substrate and connected to a second end of the conductor; wherein at least one capacitor-forming conductor, which is connected to the free terminal of the antenna main body, is provided at least one of in an interior portion of the mounting board and a surface of the mounting board.

The above-mentioned capacitor-forming conductor comprises at least one conductive pattern of linear, network and planar patterns.

Since a chip antenna or an antenna device in accordance with the present invention is provided with a capacitor-forming conductor, a capacitance in response to the shape of the capacitor-forming conductor can be formed in a capacitor between the chip antenna or antenna device and the ground of a mobile communication device provided with the chip antenna or antenna device.

Other features and advantages of the present invention will become apparent from the following description of the invention which refers to the accompanying drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a perspective view illustrating a first embodiment of a chip antenna in accordance with the present invention;

Figure 2 is an exploded isometric view of the chip antenna in Figure 1;

Figure 3 is a perspective view illustrating a modification of the chip antenna in Figure 1;

Figure 4 is a perspective view illustrating another modification of the chip antenna in Figure 1;

Figure 5 is a perspective view illustrating a second embodiment of a chip antenna in accordance with the present invention;

Figure 6 is a perspective view illustrating a third embodiment of a chip antenna in accordance with the present invention;

Figure 7 is an isometric view of a first embodiment of an antenna device in accordance with the present invention, including a perspective view of an antenna main body of the antenna device;

Figure 8 is a perspective view of a modification of the antenna main body in Figure 7;

Figure 9 is a perspective view of another modification of the antenna main body in Figure 7;

Figure 10 is a perspective view of a second embodiment of an antenna device in accordance with the present invention;

Figure 11 is a perspective view of a third embodiment of an antenna device in accordance with the present invention; and

Figures 12(a) and 12(b) are, respectively, a plan view of a conventional chip antenna and a cross-sectional view taken along section line A-A of Figure 12(a).

#### DETAILED DESCRIPTION OF EMBODIMENTS OF THE INVENTION

Embodiments in accordance with the present invention will now be described with reference to the drawings.

Figure 1 is a perspective view illustrating a first embodiment of a chip antenna in accordance with the present invention, and Figure 2 is an exploded isometric view of the chip antenna. The chip antenna 10 comprises a rectangular parallelepiped substrate 11 having a mounting surface 111, a spiral conductor 12 which is provided in the substrate 11 and has a spiral axis C parallel to the mounting surface 111, i.e., along the longitudinal direction of the substrate 11, a feeding terminal 13 formed on the surface of the substrate 11 and connected to one end of the conductor 12 for feeding a voltage to the conductor 12, and a linear capacitor-forming conductor 14 connected to the other end of the conductor 12. A capacitor is formed between the capacitor-forming conductor 14 and the ground (not shown in the drawing) of a mobile communication device, such as a ground of a circuit mounting board on which the chip antenna 10 is mounted, provided with the chip antenna 10.

The substrate 11 may be a laminate of rectangular sheet layers 15a to 15c comprising a dielectric material having a relative dielectric constant of approximately 6.1 and containing barium oxide, aluminum oxide and silica as major components. Linear and/or bent conductive patterns 16a to 16g comprising copper or a copper alloy are formed on the surfaces of the sheet layers 15a and 15b by printing, evaporation, bonding, or plating. The linear capacitor-forming conductor 14 is formed on the surface of the sheet layer 15a by printing, evaporation, bonding or plating. Via holes 17 are formed at given positions in the sheet layer 15b, corresponding to both ends of the conductive patterns 16e to 16g, in the vertical direction.

The sheet layers 15a to 15c are laminated and baked, and the conductive patterns 16a to 16g are connected to each other through the via holes 17 to form the spiral conductor 12 having a rectangular cross-section along the longitudinal direction of the substrate 11. The linear capacitor-forming conductor 14 is formed inside the substrate 11.

One end of the conductor 12, i.e., one end of the conductive pattern 16a, [is extracted] extends to the surface of the substrate 11 to form a feeding section 18 which is connected to the feeding terminal 13 formed on the surface of the substrate 11 for applying a voltage to the conductor 12. The other end of the conductor 12, i.e., the other end of the conductive pattern 16d, is connected to the capacitor-forming conductor 14 inside the substrate 11.

Figures 3 and 4 are perspective views of modifications of the chip antenna shown in Figure 1. A chip antenna 10a shown in Figure 3 is provided with a rectangular parallelepiped substrate 11a, a spiral conductor 12a wound around the surfaces of the substrate 11a in the longitudinal direction of the substrate 11a, a feeding terminal 13a formed on a sub-

strate 11a and connected to one end of the conductor 12a for feeding a voltage to the conductor 12a, and a linear capacitor-forming conductor 14a formed inside the substrate 11a and connected to the other end of the conductor 12a through a via hole 17a. A capacitor is formed between the capacitor-forming conductor 14a and the ground (not shown in the drawing) of a mobile communication device provided with the chip antenna 10a. In this embodiment, the spiral conductor can be readily formed on the surfaces of the substrate by screen printing, and thus the chip antenna can be produced by simplified production processes.

A chip antenna 10b shown in Figure 4 comprises a rectangular parallelepiped substrate 11b, a meandering conductor 12b formed on a surface (one of the main surfaces) of the substrate 11b, a feeding terminal 13b formed on the surface of the substrate 11b and connected to one end of the conductor 12b for feeding a voltage to the conductor 12b, and a linear capacitor-forming conductor 14b formed on the surface of the substrate 11b and connected to the other end of the conductor 12b through a via hole 17b. A capacitor is formed between the capacitor-forming conductor 14b and the ground (not shown in the drawing) of a mobile communication device provided with the chip antenna 10b. In this embodiment, since the meandering conductor is formed on only one main surface, a thickness reduction of the substrate, and thus a thickness reduction of the antenna itself can be achieved. The meandering conductor may also be provided inside the substrate.

Figure 5 is a perspective view of a second embodiment of a chip antenna in accordance with the present invention. The chip antenna 20 has a rectangular network capacitor-forming conductor which is different from the linear capacitor-forming conductor in the chip antenna 10. The chip antenna 20 comprises a rectangular parallelepiped substrate 11, a spiral conductor 12 wound inside the substrate 11 along the longitudinal direction, a feeding terminal 13 formed on the surface of the substrate 11 and connected to one end of the conductor 12 for applying a voltage to the conductor 12, and a rectangular network capacitor-forming conductor 21 formed inside the substrate 11 and connected to the other end of the conductor 12. A capacitor is formed between the capacitor-forming conductor 21 and the ground (not shown in the drawing) of a mobile communication device provided with the chip antenna 20. The rectangular network capacitor-forming conductor 21 can be formed by, for example, connecting linear conductive patterns, which are formed on a plurality of sheet layers, through via holes.

Figure 6 is a perspective view of a third embodiment of a chip antenna in accordance with the present invention. The chip antenna 30 has a rectangular planar capacitor-forming conductor which is different from the linear capacitor-forming conductor in the chip antenna 10. The chip antenna 30 comprises a rectangular parallelepiped substrate 11, a spiral conductor 12 wound inside the substrate 11 along the longitudinal direction, a feeding terminal 13 formed on the surface of the substrate 11 and connected to one end of the conductor 12 for applying a voltage to the conductor 12, and a rectangular planar capacitor-forming conductor 31 formed inside the substrate 11 and connected to the other end of the conductor 12. A capacitor is formed between the capacitor-forming conductor 31 and the ground (not shown in the drawing) of a mobile communication device provided with the chip antenna 30. The rectangular planar capacitor-forming conductor 31 can be formed, for example, by laminating a plurality of sheet layers each having openings filled with a conductive paste.

Table 1 shows resonance frequencies  $f$  (GHz) and bandwidths BW (MHz) which were observed for the chip antennas 10, 20 and 30, as well as the conventional chip antenna 1 shown in Figure 12 for comparison. These chip antennas 10, 20, 30 and 1 have an outer size of 6.3 mm by 5 mm by 2.5 mm. The relative dielectric constant of the dielectric material used in the substrates is approximately 6.1.

Table 1

	$f$ (GHz)	BW (MHz)
Chip antenna 10 (linear)	1.91	79
Chip antenna 20 (network)	1.86	91
Chip antenna 30 (planar)	1.87	100
Chip antenna 1 (conventional)	1.92	35

The results in Table 1 demonstrate that the chip antennas 10, 20 and 30 in accordance with the present invention have bandwidths greater than twice that of the conventional chip antenna 1 at frequency resonances of approximately 1.9 GHz. The results also demonstrate that the bandwidth increases as the area of the capacitor-forming conductor increases, and thus the capacitance formed between the capacitor-forming conductor and the ground of a mobile communication device increases, because the planar capacitor-forming conductor has a maximum bandwidth, and the network capacitor-forming conductor has a broader bandwidth compared to the linear capacitor-forming conductor. Since it is considered that the chip antennas 10, 20 and 30 cause series resonance of the inductance of the conductor with

the capacitor formed between the capacitor-forming conductor and the ground, the resonance frequency  $f$  and the bandwidth  $BW$  are determined by the following equations:

$$f = 1/(2\pi \cdot (L \cdot C)^{1/2}) \quad (3)$$

$$BW = k \cdot (C/L)^{1/2} \quad (4)$$

wherein  $L$  is the inductance of the conductor,  $C$  is the capacitance of the capacitor formed between the capacitor-forming conductor and the ground, and  $k$  is a constant of proportionality.

When the capacitance  $C$  between the capacitor-forming conductor and the ground increases, the inductance  $L$  of the conductor must be reduced at a constant frequency resonance  $F$  as deduced from the equation (3). A chip antenna having a broad bandwidth can therefore be achieved by increasing the capacitance  $C$  formed between the capacitor-forming conductor and the ground and by decreasing the inductance  $L$  of the conductor as deduced from the equation (4).

According to the structures of the chip antennas in the first to third embodiments, the capacitance formed between the capacitor-forming conductor and the ground of a mobile communication device provided with the chip antenna is capable of achieving compact chip antennas having broad bandwidths.

Miniaturization of chip antennas is capable of achieving miniaturized mobile communication devices, such as pagers, personal handyphone systems (PHSs), and specified low power radio communication systems.

The network capacitor-forming conductor having an increased area in the chip antenna shown in the second embodiment can increase the capacitance formed between the capacitor-forming conductor and the ground of a mobile communication device provided with the chip antenna. The chip antenna in the second embodiment therefore has a bandwidth which is approximately 15% broader than that in the first embodiment. Thus, mobile communication devices having broader bandwidths can be achieved.

The planar capacitor-forming conductor having a further increased area in the chip antenna shown in the third embodiment can further increase the capacitance formed between the capacitor-forming conductor and the ground of a mobile communication device provided with the chip antenna. The chip antenna in the third embodiment therefore has a bandwidth which is approximately 27% broader than that in the first embodiment. Thus, mobile communication devices having broader bandwidths can be achieved.

Figure 7 is an isometric view of a first embodiment of an antenna device in accordance with the present invention, including a perspective view of an antenna main body of the antenna device. The antenna device 40 comprises an antenna main body 41 and a mounting board 42 for mounting the antenna main body 41.

The antenna main body 41 is preferably made of a dielectric material comprising barium oxide, aluminum oxide and silica and having a relative dielectric constant of approximately 6.1, and comprises a rectangular parallelepiped substrate 43 having a mounting surface 431, a spiral conductor 44, which preferably comprises copper or a copper alloy, wound inside the substrate 43 and having a wound axis  $C$  parallel to the mounting surface 431, i.e., along the longitudinal direction of the substrate 43, a feeding terminal 45 formed on the surface of the substrate 43 and connected to one end of the conductor 44 for applying a voltage to the conductor 44, and a free terminal 46 formed on the substrate 43 and connected to the other end of the conductor 44.

The mounting board 42 may be formed of a plastic plate or the like and is provided with a linear capacitor-forming conductor 47 thereon having a land 47a connected to the free terminal 46 of the antenna main body 41, a transmission line 48 having a land 48a connected to the feeding terminal 45 of the antenna main body 41 at one end and a power unit  $V$  at the other end for applying a voltage to the antenna main body 41, and a ground electrode 49. The linear capacitor-forming conductor 47 is formed by printing, evaporation, bonding or plating.

In such a configuration, a capacitor is formed between the capacitor-forming conductor 47 and the ground of a mobile communication device provided with the antenna 40, for example, the ground electrode 49 of the mounting board 42.

Figures 8 and 9 are perspective views of modifications of the antenna main body shown in Figure 7. The antenna main body 41a shown in Figure 8 comprises a rectangular parallelepiped substrate 43a, a spiral conductor 44a wound around the surfaces of the substrate 43a in the longitudinal direction of the substrate 43a, a feeding terminal 45a formed on a surface of the substrate 43a and connected to one end of the conductor 44a for applying a voltage to the conductor 44a, and a free terminal 46a formed on the surface of the substrate 43a and connected to the other end of the conductor 44a. The feeding terminal 45a is connected to the land 48a of the transmission line 48 on the mounting board 42 shown in Figure 7, and the free terminal 46a is connected to the land 47a of the capacitor-forming conductor 47 on the mounting board 42. In this case, since the spiral conductor can be simply formed on the surfaces of the substrate by screen printing or the like, the antenna main body can also be produced by a simplified process.

The antenna main body 41b shown in Figure 9 comprises a rectangular parallelepiped substrate 43b, a meandering conductor 44b formed on a surface of the substrate 43b, a feeding terminal 45b formed on the surface of the sub-

strate 43b and connected to one end of the conductor 44b for feeding a voltage to the conductor 44b, and a free terminal 46b formed on the surface of the substrate 43b and connected to the other end of the conductor 44b. The feeding terminal 45b is connected to the land 48a of the transmission line 48 on the mounting board 42 shown, and the free terminal 46b is connected to the land 47a of the capacitor-forming conductor 47 on the mounting board 42. In this case, since the meandering conductor is formed on only one main surface, the thickness reduction of the substrate, and thus the thickness reduction of the antenna itself can be achieved. The meandering conductor may also be provided inside the substrate.

Figure 10 is an isometric view of a second embodiment of an antenna device in accordance with the present invention. The antenna device 50 is provided with a rectangular network capacitor-forming conductor on the mounting board instead of the linear capacitor-forming conductor in the first embodiment. The antenna device 50 comprises an antenna main body 41, a mounting board 42 for mounting the antenna main body 41, and a rectangular network capacitor-forming conductor 51 provided with a land (not shown in the drawing) which is connected to the free terminal 46 of the antenna main body 41 formed on the mounting board 42. In such a configuration, a capacitor is formed between the capacitor-forming conductor 51 and the ground of a mobile communication device provided with the antenna device 50, for example, the ground electrode 49 of the mounting board 42. The rectangular network capacitor-forming conductor 51 is formed by printing, evaporation, bonding or plating.

Figure 11 is an isometric view of a third embodiment of an antenna device in accordance with the present invention. The antenna device 60 is provided with a rectangular planar capacitor-forming conductor on the mounting board instead of the linear capacitor-forming conductor in the first embodiment. The antenna device 60 comprises an antenna main body 41 and a mounting board 42 for mounting the antenna main body 41, and the rectangular planar capacitor-forming conductor 61 provided with a land (not shown in the drawing), which is connected to the free terminal 46 of the antenna main body 41 formed on the mounting board 42. In such a configuration, a capacitor is formed between the capacitor-forming conductor 61 and the ground of a mobile communication device provided with the antenna device 60, for example, the ground electrode 49 of the mounting board 42. The rectangular planar capacitor-forming conductor 61 is formed by printing, evaporation, bonding or plating.

According to the configurations shown in the first to third embodiments, a compact antenna device having a broad bandwidth can be achieved as in the above-mentioned chip antennas by forming a capacitor between the capacitor-forming conductor and the ground of a mobile communication device provided with the antenna device.

Miniaturization of antenna devices is capable of achieving miniaturized mobile communication devices, such as pagers, personal handyphone systems (PHSs), and specified low power radio communication systems.

The network capacitor-forming conductor having an increased area in the antenna device shown in the second embodiment can increase the capacitance formed between the capacitor-forming conductor and the ground of a mobile communication device provided with the antenna device. The antenna device in the second embodiment therefore has a bandwidth broader than that in the first embodiment. Thus, mobile communication devices having broader bandwidths can be achieved.

The planar capacitor-forming conductor having a further increased area in the antenna device shown in the third embodiment can further increase the capacitance formed between the capacitor-forming conductor and the ground of a mobile communication device provided with the antenna device. The antenna device in the third embodiment therefore has a bandwidth broader than that in the first embodiment. Thus, mobile communication devices having broader bandwidths can be achieved.

The substrates of the above-mentioned chip antennas and antenna devices may be made of a dielectric material comprising barium oxide, aluminum oxide and silica as major components. The substrate, however, is not limited to this dielectric material, and may be made of a dielectric material comprising titanium oxide and neodymium oxide as major components, a magnetic material comprising nickel, cobalt and iron as major components, or a combination of a dielectric material and a magnetic material.

Each of the chip antennas and the antenna main bodies has one conductor in the above-mentioned embodiments. A chip antenna or antenna main body may be provided with a plurality of conductors disposed parallel to each other. The chip antenna or antenna main body has a plurality of resonance frequencies in response to the number of the conductors, and can act as a multiband antenna.

A linear capacitor-forming conductor is described above. Curved, meandering or serrate capacitor-forming conductors can also be used. The network or planar capacitor-forming conductor may have a circular, elliptical or polygonal shape instead of the rectangular shape described above.

The capacitor-forming conductors in the above-mentioned chip antennas are provided inside the substrate. The capacitor-forming conductor may be provided on the surface of the substrate.

The capacitor-forming conductors in the above-mentioned antenna devices are provided on the mounting board. The capacitor-forming conductor may be provided inside the mounting board.

Although the conductor is provided inside or on the substrate in the above-mentioned embodiments, a spiral or meandering conductor may be formed both on and inside the substrate.

According to the present invention, a compact chip antenna and antenna device having a broad bandwidth can be achieved by forming a capacitor between the capacitor-forming conductor and the ground of a mobile communication device provided with the chip antenna or antenna device.

Miniaturization of the chip antenna or antenna device is capable of achieving miniaturized mobile communication devices, such as pagers, personal handyphone systems (PHSs), and specified low power radio communication systems.

Although the present invention has been described in relation to particular embodiments thereof, many other variations and modifications and other uses will become apparent to those skilled in the art. Therefore, the present invention should be limited not by the specific disclosure herein, but only by the appended claims.


## Claims

1. A chip antenna (10; 10a; 10b; 20; 30) comprising a substrate (11) comprising at least one material selected from a dielectric material and a magnetic material, at least one conductor (12; 12a; 12b) formed at least one of in an interior portion of the substrate (11) and on a surface of said substrate (11), at least one feeding terminal (13; 13a; 13b) provided on the surface of said substrate (11) and connected to a first end of said conductor (12; 12a; 12b) for applying a voltage to said conductor, and at least one capacitor-forming conductor (14; 14a; 14b; 21; 31) provided at least one of in the interior of said substrate (11) and on the surface of said substrate and connected to a second end of said conductor (12; 12a; 12b).
2. An antenna device (40; 50; 60) comprising an antenna main body (41; 41a; 41b) and a mounting board (42) for mounting said antenna main body (41; 41a; 41b); said antenna main body comprising a substrate (43; 43a; 43b) comprising at least one material selected from a dielectric material and a magnetic material, at least one conductor (44; 44a; 44b) formed at least one of in an interior portion of the substrate (43; 43a; 43b) and on a surface of said substrate, at least one feeding terminal (45; 45a; 45b) provided on the surface of said substrate (43; 43a; 43b) and connected to a first end of said conductor (44; 44a; 44b) for applying a voltage to said conductor, and at least one free terminal (46; 46a; 46b) provided on the surface of said substrate (43; 43a; 43b) and connected to a second end of said conductor (44; 44a; 44b);  
wherein at least one capacitor-forming conductor (47; 51; 61), which is connected to said free terminal (46; 46a; 46b) of said antenna main body (41; 41a; 41b), is provided at least one of in an interior portion of the mounting board (42) and on a surface of said mounting board (42).
3. The chip antenna of claim 1 or the antenna device of claim 2, wherein said capacitor-forming conductor comprises a conductive pattern comprising at least one of a linear pattern (14; 14a; 14b; 47), network pattern (21; 51) and planar pattern (31; 61).
4. The chip antenna of claim 1 or 3 or the antenna device of claim 2 or 3, wherein the conductor (12; 12a; 44; 44a) comprises a spiral shaped conductor.
5. The chip-antenna of claim 1 or 3 or the antenna device of claim 2 or 3, wherein the conductor (12b; 14) comprises a meandering conductor disposed essentially in a plane.
6. The chip antenna of one of the preceding claims or the antenna device of one of the preceding claims, wherein the capacitor-forming conductor (14; 14a; 14b; 47) comprises a linear portion extending from the at least one conductor (12; 12a; 12b; 44).
7. The chip antenna of one of claims 1 and 3 to 5 or the antenna device of one of claims 2 to 5, wherein the capacitor-forming conductor (31; 51) comprises a planar portion extending from and coupled to said at least one conductor (12; 44).
8. The chip antenna of one of the preceding claims or the antenna device of one of the preceding claims, wherein the substrate (11; 43; 43a; 43b) comprises a plurality of layers (15a; 15b; 15c).
9. The chip antenna or the antenna device of claim 8, wherein selected ones of the layers (15a; 15b) comprising at least one portion of the conductor, at least one layer (15b) comprising a conductive through hole (17) connecting respective ones of the conductor portions together when the plurality of layers (15a; 15b; 15c) are laminated together, thereby forming the at least one conductor (12).

EP 0 831 546 A2

10. The chip antenna (20; 30) of claim 9, wherein the capacitor forming conductor comprises a plurality of conductive layers disposed on respective layers in contact with each other through a plurality of conductive through-holes when the layers are laminated together.
- 5 11. The chip antenna of one of the preceding claims or the antenna device of one of the preceding claims, wherein the dielectric material comprises barium oxide, aluminum oxide and silica.
12. The chip antenna of one of claims 1 and 3 to 10 or the antenna device of one of claims 2 to 9, wherein the substrate (11; 43; 43a; 43b) comprises a dielectric material comprising titanium oxide and neodymium oxide.
- 10 13. The chip antenna of one of claims 1 and 3 to 10 or the antenna device of one of claims 2 to 9, wherein the substrate (11; 43; 43a; 43b) comprises a magnetic material comprising nickel, cobalt and iron.
14. The chip antenna of one of the preceding claims or the antenna device of one of the preceding claims, wherein the substrate (11; 43; 43a; 43b) comprises a combination of a dielectric material and a magnetic material.
- 15 15. The chip antenna of claim 1 or 3 or the antenna device of claim 2 or 3, wherein the conductor (12a; 44a) is disposed spirally around the surface of the substrate (11; 43a).
- 20 16. The chip antenna of claim 5 or the antenna device of claim 5, wherein the meandering conductor (12b; 44b) is disposed on a surface of the substrate (11; 43b).
17. The antenna device of one of the preceding claims, further comprising a ground conductor (49) provided on said mounting board (42) for providing a second capacitor-forming conductor forming a capacitor with the capacitor-forming conductor (47; 51; 61).
- 25





**FIG. 1**




FIG. 2

**BEST AVAILABLE COPY**




FIG. 3




FIG. 4




FIG. 5




FIG. 6

BEST AVAILABLE COPY




FIG. 7




FIG. 8




FIG. 9




FIG. 10

BEST AVAILABLE COPY




FIG. 11

BEST AVAILABLE COPY




FIG. 12

BEST AVAILABLE COPY





(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

**EP 0 831 546 A3**

(12)

## EUROPEAN PATENT APPLICATION

(88) Date of publication A3:  
01.04.1998 Bulletin 1998/14

(51) Int. Cl.<sup>6</sup>: **H01Q 1/36**, **H01Q 1/38**

(43) Date of publication A2:  
25.03.1998 Bulletin 1998/13

(21) Application number: **97116099.9**

(22) Date of filing: **16.09.1997**

(84) Designated Contracting States:  
**AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC  
NL PT SE**  
Designated Extension States:  
**AL LT LV RO SI**

(30) Priority: **20.09.1996 JP 250142/96**

(71) Applicant:  
**MURATA MANUFACTURING CO., LTD.**  
**Nagaokakyo-shi Kyoto-fu 226 (JP)**

(72) Inventors:  
• **Suesada, Tsuyoshi**  
**Nagaokakyo-shi, Kyoto-fu (JP)**  
• **Kanba, Seiji**  
**Nagaokakyo-shi, Kyoto-fu (JP)**  
• **Tsuru, Teruhisa**  
**Nagaokakyo-shi, Kyoto-fu (JP)**


(74) Representative:  
**Schoppe, Fritz, Dipl.-Ing.**  
**Schoppe & Zimmermann**  
**Patentanwälte**  
**Postfach 71 08 67**  
**81458 München (DE)**

### (54) Chip antenna and antenna device

(57) [Purpose] To provide a compact chip antenna and antenna device having a broad bandwidth.

[Construction] A chip antenna 10 is provided with a rectangular parallelepiped substrate 11 composed of a dielectric material (relative dielectric constant: ca. 6.1) containing barium oxide, aluminum oxide and silica as major components, a spiral conductor 12 wound in the substrate 11 along the longitudinal direction of the substrate 11, a feeding terminal 13 formed on the surface of the substrate 11 and connected to one end of the conductor 12 for applying a voltage to the conductor 12, and a linear capacitor-forming conductor 14 formed in the substrate 11 and connected to the other end of the conductor 12. In such a configuration, a capacitor is formed between the capacitor-forming conductor 14 and the ground (not shown in the drawing) of a mobile communication device provided with a chip antenna 10.

[Figure 1]



**EP 0 831 546 A3**



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 97 11 6099

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X	EP 0 621 653 A (MURATA MANUFACTURING CO) 26 October 1994 * column 9 - column 10, line 14; figures 5A-5C * * column 11, line 17-53; figure 8 * * column 16, line 45 - column 18, line 13; claims 1,35-40; figures 16-19 * * abstract *	1-3,6,7,14,17	H01Q1/36 H01Q1/38
E	EP 0 790 665 A (MURATA MANUFACTURING CO) * abstract; claims 1-14,16-21 * * column 3, line 3-35; figures 1,2 * * column 4, line 9-34; figures 6,7 *	1-17 1-17	
X	EP 0 802 577 A (MURATA MANUFACTURING CO) * abstract; claims 1,3,4,6-10.13 * * column 3, line 22 - column 4, line 3; figures 1,2 * * column 4, line 13-31; figure 4 *	1,3-16 1,3-16	
E	EP 0 743 699 A (MURATA MANUFACTURING CO) 20 November 1996 * the whole document *	1-17	TECHNICAL FIELDS SEARCHED (Int.Cl.6) H01Q
E	EP 0 759 646 A (MURATA MANUFACTURING CO) 26 February 1997 * the whole document *	1-17	
E	EP 0 762 539 A (MURATA MANUFACTURING CO) 12 March 1997 * the whole document *	1-17	
A	US 5 014 071 A (KING JEFFREY S) 7 May 1991 * column 2, line 60-68; figure 1 * * abstract; claim 1 *	1,2,14	
The present search report has been drawn up for all claims			
Place of search MUNICH		Date of completion of the search 27 January 1998	Examiner Felgel-Farnholz, W-D
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons &amp; : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03 82 (P04C01)



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 97 11 6099

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
A	EP 0 687 030 A (MURATA MANUFACTURING CO) 13 December 1995 * column 8, line 33 - column 10, line 39; figures 6-8 * * abstract * -----	1-17	
			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
The present search report has been drawn up for all claims			
Place of search <b>MUNICH</b>		Date of completion of the search <b>27 January 1998</b>	Examiner <b>Felgel-Farnholz, W-D</b>
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03 82 (P04C01)

**THIS PAGE BLANK (USPTO)**